



# CM30CS

CM30CS is designed for service van use. CM30CS is manually operated and easy to use and it comes with a fume exhaust connection.

12 or 24V operated versions available.

Please also see product cards for other CM30/35 configurations.

## TECHNICAL DATA

Max. hose size (inch) <sup>1)</sup>	2 / 1 1/4
Diameter (blade) external	300x3
Diameter (blade) internal	30
Max. hose OD	70
Exhaust outlet OD (mm)	60
Motor Power (kW) <sup>2)</sup>	2.2 / 1.5
Motor Power (HP) <sup>2)</sup>	3.0 / 2.0
Velocity, 50Hz	2750
Velocity, 60Hz	3370

## DIMENSIONS (LxWxH)

mm	600x503x739
inch	23.6x19.8x29.1

## WEIGHT

kg/lbs	37/81,4
--------	---------


1) Hydraulic hose, 1-2 wire / 4 wire  
2) 12V / 24V. Overload controlled.

## STANDARD FEATURES

Toothed blade

## OPTIONS

Smooth blade



Toothed blade  
as a standard feature.



Smooth blade  
as an option.

**FURTHER INFO ON OPTIONS,  
PLEASE REVERT TO SPECIFIC PRODUCT CARD**

**POWERCO.LILLBACKA.COM    LILLBACKAUSA.COM**